

SHARP GEN3 DIM



PREMIUM RETROFIT SOLUTION OF HALOGEN

- L70B50 Lifetime up to 40,000hrs, 5 years limited warranty
- Compatible with both leading edge and trailing edge dimmers
- Percent flicker < 7%
- CRI 97, SDCM 3
- 90% energy saving compared to standard halogen spots
- Switching cycles at the rate of 30s ON/30s OFF = 100,000 cycles

Light Color



Typical CRI: 97(Ra) R9>80

Housing Material

Heatsink- Aluminum
Lens - PC

Finishing - Silver


IP Rating

IP42

Dimmability

Compatible with most
leading edge or trailing edge dimmers

Dimension Drawings



EAN13 Code	Watt*	Volt	Flux*	CCT	Angle	CRI*	SDCM	Dimmable
5703011101005	5,5W	220-240Vac	410lm	2700K	50D	Ra97	3 Steps	Yes
5703011102002	5,5W	220-240Vac	430lm	3000K	50D	Ra97	3 Steps	Yes

* ALED maintains a tolerance of ±10% on flux and power measurements, and ±2 on CRI in any condition

** Testing voltage is 230Vac 50/60Hz , ambient temperature 25 Degrees Celsius

** 5 years warranty period is not applicable for commercial use

