

OPERATING MANUAL Charlotte PRO

Important: Please read the instruction manual carefully prior to installation and keep it for future reference.



105mm	
340mm ———	

Ordering code	Product	Power	Function
	Fitting series	(W)	Description
Charlotte PRO	Charlotte	15	Basic LED

Mounting: Wall or Ceiling

Light features: CRI(Ra): >80Ra Life Time: 50,000hrs

Light Source: LED SMD2835 Input:220V-240VAC 50/60Hz 0/C180 __ 00/C270 __


Accessories

No.	Pic.	Qty.	Usage	
1	()	3 Fix light		
2	=	3	Plastic parts	
3	0	3	Plastic washer	


Color temperature code:

Code	Color temperature	CCT(K)	Lumen
30K	Warm White	3000	1200
40K	Natural White	4000	1275
50K	Cool White	5000	1330


CCT:




Installation:




Remove the cover.




Unlock the legs on the PCB board.



Fix the housing onto the ceiling.




Wire connection.



Close the cover.

Wiring




Maintenance

- 1. Cut off the main power first
- 2. Don't touch LEDs while maintaining or cleaning
- 3. Don't use chemicals to clean the fixture.







Environmental protection: waste electrical products should not be disposed of with household waste. Please recycle where facilities exist. Check with your local authority or retailer for recycling advice.

Caution:

- 1. The product must be installed by professional technicians and the power supply must be cut off before installation.
- 2. The installation wiring must be at least 0.75mm² and wired in accordance with the latest IEE electrical regulations or the national requirements.
- 3. Do not touch the electronic circuit and its components.
- 4. Contact an authorised technical service centre for any repairs required and use only original spare parts.
- 5. Do not touch LEDs while installing or maintaining.
- 6. The LED light source can not be replaced.

















