



Product information

Jackson er hurtig og nem at montere og installere. Der er godt med plads i installationsboksen i begge ender..

Features

- * Kelvingraden indstilles nemt på dip-switch
- * L90 50.000 timer (Ta 25°C)
- * L80 100.000 timer (Ta 25°C)
- * Wattagen indstilles nemt på dip-switch

Product data

General Information

Light source type	LED
Number of LED module	1 pcs
Beam angle of LED module	120°
Color temperature	3000K-4000K-5000K selectable
CRI	80
LED module replaceable	yes
Number of LED driver	1 unit
Driver included	Yes
Driver replaceable	Yes
L90 lifetime of LED module	50,000 hrs
L80 lifetime of LED module	100,000 hrs
LED module lumen	9600 lm (max)

Operating and Electrical

Input Voltage	220-240 Vac
Input frequency	50 to 60 Hz
System wattage	30W-38W-45W-53W-60W selectable
Inrush current	21A
Inrush time	272us
Power factor	0.95
Leakage current	<0.5mA
Max. units per circuit B16 breaker	16pcs
Max. units per circuit C16 breaker	27pcs
Surge protection	2.5KV L-N
Ambient temperature range	-20°C to + 40°C
Performance ambient temperature Tq	+25°C

SDCM	5 steps
Optical type	PC cover
Control and dimming	Non-dimmable
Connection type	5 pole connector
Protection class IEC	Safety class I
Glow-wire test	650°C, 30 s
UGR	25
PstLM	
SVM	
CE Mark	Yes
EU RoHS compliant	Yes
Net weight (piece)	1.73Kg

Dimension

Overall length	1500 mm
Overall width	102 mm
Overall height	54mm

Mechanical and Housing

Housing material	PC
Optical material	PC
Housing color	White
Heatsink material	Aluminum
Ingress protection code	IP65
Mech. impact protection code	IK 08

Remarks

LED driver failure rate at 50,000hrs	5 %
Power consumption tolerance	± 7 %

Product picture



Dimensional drawing



	L	W	H
0.6M	619mm	102mm	54mm
1.2M	1219mm	102mm	54mm
1.5M	1500mm	102mm	54mm