

COB LED SRTIP LIGHT PRODUCT SPECIFICATION

Key Feature

- LM-80 approved LED
- 50,000 hours Lifetime, 5 years warranty
- Kelvin : 2200K
- Light Spotless,flexible
- CRI: Ra>90








CE

E473513

Drawing:



Electric (24V)

Notice:

Safety Input Voltage: DC 24V

Size of each section is 100mm andcuttingat "scissorssymbol" place.

LED Strip length's length tolerance is $\pm 0.2\%$ mm, width tolerance is ± 0.2 mm.

Optical

LED type:	Flip Chip	Input current/m:	0.417A/m
Color rending index:	Ra>90	Input Voltage:	DC24V
CCT:	2200K	Voltage Power/m:	10W/m
		Static Electricity:	1000V(ESD)
Irritation angle:	180°	LEDs/meter:	480LEDs/m
Light Effciency:	80 Lm/w	Size of section:	50mm
		LEDs of section:	48LEDs

Others

Energy grade:	A+	
Warranty:	5 years	
Working hour:	50,000hrs lifetime for Tc<70°C	
Working temperature:	-20°C ~ +105°C	
Waterproof Rate:	IP67	*


Descriptions:

- LED Strip can be used in many kinds of places as decorative lighting/backlight/, such as Ceiling trough, Staircase, Hall walkway, Billboard,
- 100% of the lamps will be tested and keep lighting for 24h testing its quality reliability, and we also test it temperature after 24 hours's lighting;
- We can provide with different Custom products, such as printing Customer LOGO on FPC, Custom Aluminum Foil Bag Custom carton box/connector/DC cable/, Customs FPC design/color/width etc.




CE

Waterproof Rate :



Wiring diagram application :









4 / 5

3M Adhesive Tape











≤50 mm diameter of wrapped object prohibited



Touching LED, pls wear the electrostatic ring for avoiding ESD



Satety Information

Application notes for led exiable strip

In order to drive LED flexible strip lights safely, it is absolutely necessary to operate them with an electronically stabilised power supply protecting against short circuits, overload and overheating.

To also ease the luminaire/installation approval, electronic control gear, power supply and all electronic accessories for LED or LED modules should carry "CE, or UL" mark and meet the latest safety standard.

- Please use 24VDC isolated power supply to drive the led strip, and the constant voltage source ripple less than 5%. Can't step-down the power by resistance-capacitance and nun-isolated power supply driver led strip, etc.
- To ensure the longevity and reliability of the strips, please do not bend the arc diameter 60mm or less, do not fold to avoid damaging the lamp beads or broken.
- To ensure the life and environment of lights, in the use of force can not pull the power cord to avoid damage to prohibit collision LED lights.
- During the installation of positive and negative attention to the power cord, do not pick the wrong voltage power supply and the product are the same, so as to avoid damage to the product.
- LED lights should be stored in dry sealed environment, the proposed storage period should not be too long before using unpacking, the working temperature: -20 ~ + 45, Storage temperature: -0 ~ + 60, not waterproof lights band indoor use, relative humidity not higher than 70%.
- In practical applications, the power supply should leave 20% margin (recommend using only 80% of the power) in order to ensure a suf cient amount of voltage drive products
- > Do not use any acidic, alkaline adhesive securement products (including not limited to glass, plastic, etc.)

