

IP66

⚠ ZONE 2/22



Description

Linear luminaire designed for explosion hazardous areas for ATEX zone 2/22. Body made of painted steel sheet (RAL 9016) with EPDM gasket – alternatively stainless steel AISI304 or AISI316. Cover made of opal tempered safety glass. Equipped with high quality electronic components with a high lifetime of 100 000 h and an efficiency of 154 lm/W. Characterized by high splash and dust resistance IP66. Suitable for ambient temperatures from -20 °C to +60 °C. Silicone-free design. Designed to be mounted or hinged.

Specifications**Operating voltage:**

220-240 V / 50/60 Hz AC, 220-240 V DC

Source:

LED, 4000K, CRI +80, MacAdam3

Housing:

Painted steel sheet RAL 9016

Cover:

OP – tempered opal safety glass

Spotlight:

Painted steel sheet RAL 9016

Fastening:

Direct fixing to the ceiling or wall of the illuminated space, fixing to the ceiling using ceiling brackets, cable suspension on two steel lugs

Connection:

Screwless three-pole terminal block, max. wire cross-section 2.5 mm²

Standard equipment:

1x gland for cable diameter 7-12 mm, 1x gland plug, 2x hanging eye, 2x rubber gasket

Calculated lifetime – LED modules:

L80B10 Ta 40 – 70 000 h

L70B10 Ta 40 – 100 000 h

SALUKA-N-LED, MULTISALUKA-N-LED, SALUKA-N-LED-Em

(FTZU 17 ATEX 0027X)

Ex II 3G Ex nR IIC T6 Gc

Ex II 3D Ex tc IIIC T80°C Dc

On order

3000K/4000K/5000K/6500K – colour temperature

MULTI – permanent emergency lighting (1h, 3h)

EM – temporary emergency lighting (1h, 3h)

DIM – dimmable electronic ballast (DALI, DSI, 1-10V)

1/3F – single-phase or three-phase connection, max. conductor cross-section 2.5 mm²

GESIS – possibility to equip the luminaires with connectors

NEREZ – body made of stainless steel sheet AISI 304 or AISI 316 (for NEREZ version lower ambient temperature by approx. 5-10 °C)

Accessories

SALUKA ceiling fixings set (2 pcs)

Item number: **3583**

Product type: **051139**

[Catalogue sheet](#)

SALUKA stainless steel shank (diameter 50 mm)

Item number: **3589**

Product type: **051145**

[Catalogue sheet](#)

PITBUL/SALUKA boom for boom diameter 50 mm (1 piece) AISI 304

Item number: **3590**

Product type: **051146**

[Catalogue sheet](#)

SALUKA stainless steel shank (for 40 mm dia.)

Item number: **30316**

Product type: **064018**

[Catalogue sheet](#)

Set of adjustable holders SALUKA (2 pcs)

Item number: **28788**

Product type: **063754**

[Catalogue sheet](#)

Stainless steel wall arm SALUKA 60° (1 pc)

Item number: **3591**

Product type: **051147**

[Catalogue sheet](#)

© 2025 All rights reserved. VYRTYCH a.s. does not warrant the accuracy or completeness of the information provided herein and is not responsible for any events that may occur as a result of unqualified reliance on this information. The information contained herein does not constitute a commercial offer and does not form part of a quotation or contract, unless confirmed by VYRTYCH a.s..