

Outdoor luminaire for wall/ceiling installation

Minimum thickness

Material: housing in low copper content die-cast aluminium / Internal wire holder plate in 99,8 aluminium

Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket

Built-in driver

Light source: LED unit

Suitable for through wiring installation by double cable entry

No visible frontal screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):


- S Version with sensor
- D Dimmable version

|                             |                      |
|-----------------------------|----------------------|
| Dimensions                  | Ø 235 x 68 mm        |
| Light source                | LED                  |
| Wattage                     | 15 W                 |
| Power supply                | 220-240 V   50/60 Hz |
| Light source output         | 2300 lm              |
| System output               | 890 lm               |
| System efficiency           | 59 lm/W              |
| Color Rendering Index – CRI | 80                   |
| LED energy class            | C                    |
| Electrical insulation class | Class I              |
| IP rating                   | IP 65                |
| Impact resistance rating    | IK 10 (20 joules)    |
| Norms                       | EN 60598-1 +2-1      |
| Weight                      | 1.2 kg               |
| Conformity                  | CE UK<br>CA          |

## CODE OPTIONS

| FINISH |                | COLOUR TEMP. |       |
|--------|----------------|--------------|-------|
| AG     | ALUMINIUM GREY | 27K          | 2700K |
| AN     | ANTHRACITE     | 3K           | 3000K |
| BI     | WHITE          | 4K           | 4000K |

ACCESSORIES



LUNETTE THE SERIES

