

Outdoor luminaire for wall/ceiling installation

Minimum thickness

Material: housing in low copper content die-cast aluminium / Internal wire holder plate in 99,8 aluminium

Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket

Built-in driver

Light source: LED unit

Suitable for through wiring installation by double cable entry

No visible frontal screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

S Version with sensor

D Dimmable version

Dimensions	Ø 365 x 70 mm
Light source	LED
Wattage	29 W
Power supply	220-240 V 50/60 Hz
Light source output	4400 lm
System output	3250 lm
System efficiency	112 lm/W
Color Rendering Index – CRI	80
LED energy class	D
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	2.7 kg
Conformity	CE UK CA

CODE OPTIONS


FINISH

AG ALUMINIUM GREY
AN ANTHRACITE
BI WHITE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

ACCESSORIES



LUNETTE

THE SERIES

