



Outdoor projector for wall, pole and ground installation
 Adjustable hooking bracket
 Material: low copper content die-cast aluminium
 Diffuser: ultra-white transparent tempered glass, sealed to the frame
 Light source: mains voltage LED module, compatible with phase-cut dimmers / Round symmetric optics
 Supplied with 1 m cable
 Color matching side fixing screws in stainless steel
 Optional surge protection device (SPD) to be ordered separately
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
MT4 4 m cable length for pole mounting

Dimensions	Ø 270 x 347 x 68 mm
Light source	LED
Wattage	20 W
Power supply	220-240 V 50/60 Hz
Light source output	2360 lm
System output	1500 lm
System efficiency	75 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-5
Weight	3.9 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 40°
 optional optics
12 12°
90 90°

ACCESSORIES

ACCESSORIES
SPD



1965

ACCESSORIES
BURIABLE POLE H 2500



3504

ACCESSORIES
BURIABLE POLE H 3000



3505

PROTO
SINGLE POLE CONNECTION



5061

PROTO
DOUBLE POLE CONNECTION



5062

ACCESSORIES
BURIABLE POLE H 3500



3506

PROTO THE SERIES

