



Outdoor projector for wall, pole and ground installation
 Adjustable hooking bracket
 Material: low copper content die-cast aluminium
 Diffuser: ultra-white transparent tempered glass, sealed to the frame
 Built-in driver
 Light source: highly performing LED modules / Symmetric and asymmetric STRADA optics
 Supplied with 1 m cable
 Color matching side fixing screws in stainless steel
 Optional surge protection device (SPD) to be ordered separately
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D** Dimmable version
- MT4** 4 m cable length for pole mounting

Dimensions	Ø 270 x 347 x 68 mm
Light source	LED
Wattage	35 W
Power supply	220-240 V 50/60 Hz
Light source output	4212 lm
System output	3352 lm
System efficiency	96 lm/W
Color Rendering Index – CRI	80
LED energy class	D
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-5
Weight	4 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

- AG** ALUMINIUM GREY
- AN** ANTHRACITE

COLOUR TEMP.

- 27K** 2700K
- 3K** 3000K
- 4K** 4000K

OPTIC

- standard** 100°
- optional optics
- 01** 17°
- 02** 150° X 45°
- 03** 90° X 30°
- 04** 120° X 45°
- 05** 150° X 70°

ACCESSORIES

ACCESSORIES
SPD



1965

ACCESSORIES
BURIABLE POLE H 2500



3504

ACCESSORIES
BURIABLE POLE H 3000



3505

PROTO
SINGLE POLE CONNECTION



5061

PROTO
DOUBLE POLE CONNECTION



5062

ACCESSORIES
BURIABLE POLE H 3500



3506