



Physical Dimension(MM)

MODEL NO.	POWER	LIGHT SOURCE	LED COLOR	BEAM ANGLE	INPUT VOLT	CONTROL
ET-DIL2480142A	42W/36W /48W/54W	1PCS CREE COB	2700K-6500K	15°/24°/36°/60° (Lens)	AC220-240V /AC110-130V /AC110-240V	ON/OFF /Triac/0-10V/DALI
ET-DIL2480154A	42-54W				DC24V/DC48V	ON/OFF /0-10V/DALI/DMX512
ET-DIL2480142B	42W/36W /48W/54W			8-12°/22-25° /38-42°/57-63° (Reflector Cup)	AC220-240V /AC110-130V /AC110-240V	ON/OFF /Triac/0-10V/DALI
ET-DIL2480154B	42-54W				DC24V/DC48V	ON/OFF /0-10V/DALI/DMX512

Material Specifications

Front cover :Stainless steel SUS316

Housing:12# Die-casting grey powder coated aluminum.T=60-80µm Adhesion of ISO class 1/ASTM class 4B high temperature painting

Driver:Constant current output,Constant current output

Glass:Step tempered glass

Mounting sleeve:ABS

COB+Lens



Mounting Sleeve



Square Frame



Features



High colour rendering index



Excellent thermal management



Dimmable versions available



Available in round or square